# **Product information**

## **Digital micrometer Micromar 40 EWRi-S**

#### **Product features**

- With blade-type measuring surfaces
- · High contrast digit display
- Stainless spindle is hardened throughout and ground
- QUICK DRIVE
- · Sliding spindle
- Ratchet is integrated in the thimble
- Lacquered steel frame, heat insulated



RESET (set display to zero),
ABS (display can be set to zero
without losing reference to
ORIGIN), mm/inch, ORIGIN (for
entering a numerical value),
LOCK function (key lock), TOL
(Tolerance and Warning Limits
Input), HOLD (freeze current
measured value), DATA (data
transmission), Bi-directional
data interface (for data retrieval,
transfer of parameters, remote
control, individual function locks
via MarCom software)

#### Package contains

setting standard (measuring range of 25-50 mm), battery, test certificate, instruction manual, case

#### **Application**

For measuring recesses, grooves, etc.




Item no.: 4157141

### **Technical data**

Measuring range mm	0 - 25 mm
Measuring range	0 - 1"
Resolution mm/inch	0.001 / .00005"
Error limit µm	4
Measuring force (N)	5 - 10
Battery type	CR 2032 (3V Lithium)
Material Contact surface	hardened steel
Spindle diameter	6.5
Spindle thread pitch_mm	5

#### **Dimensions**

Dimensions b in mm	11.5
Dimensions a in mm	32
Dimensions c in mm	57



#### **Accessories**

Order no.
4102220